

Project Name

Location

Prepared By



Notes

[www] 03-31-2023 09:32:29

General	
Status	Active
Watts	24W
Incandescent Equivalent	100W
Fluorescent Equivalent	38W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	72
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	3200L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	70
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	1.1

Additional Information	
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp