

Project Name

Location

Prepared By



## SATCO S11950

7T8/LED/18-830/BP

### Notes

(www) 08-04-2023 00:37:21

### General

|                         |               |
|-------------------------|---------------|
| Status                  | Active        |
| Watts                   | 7W            |
| Incandescent Equivalent | 75W           |
| Fluorescent Equivalent  | 15W           |
| Volts                   | 120V-277V     |
| Ballast Type            | Type B        |
| Shape                   | T8            |
| Base                    | Medium Bi Pin |
| ANSI Base               | G13           |
| Nominal Length          | 18            |
| Finish                  | Frost         |
| CCT (Kelvin)            | 3000K         |
| Temperature             | Warm White    |
| CRI                     | 80+           |
| Lumens                  | 700L          |
| Beam Spread             | 160           |
| Dimmable                | Non-Dimmable  |
| Hours Rated             | 50000         |
| Product Category        | Linear        |
| Technology              | LED           |

### Electrical

|                         |                             |
|-------------------------|-----------------------------|
| Ballasting Requirements | Ballast Bypass              |
| Operating Frequency     | 50/60Hz                     |
| Power Factor            | 0.9                         |
| THD                     | 25%                         |
| Operating Temperature   | -25C (-13F) to +40C (+104F) |

### Physical

|               |                 |
|---------------|-----------------|
| MOL           | 17.8            |
| MOD           | 1.1             |
| Material      | Glass / Plastic |
| Lens Finish   | Frost           |
| Lens Material | Glass           |
| Housing Color | White           |
| Weight (lb.)  | 0.22            |

### Additional Information

|                            |                                      |
|----------------------------|--------------------------------------|
| Shatter-Proof Type         | PET Coated                           |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes                                  |
| Warranty                   | 5-Years                              |

### Compliance

|                      |  |
|----------------------|--|
| Safety Listing       | cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component |
| Location Rating      | Damp   |
| DLC Approved         | No   |
| California Status    | Lawful for sale in California  |
| Title 20 / 24 Status | Lawful for sale  |
| Colorado Status      | Lawful for sale  |
| Hawaii Status        | Lawful for sale  |
| Nevada Status        | Lawful for sale  |
| Vermont Status       | Lawful for sale  |
| Washington Status    | Lawful for sale  |
| RoHS Compliant       | Yes  |
| FCC Compliant        | Yes  |
| NSF Approved         | ETL Sanitation listed (conforms to NSF)  |
| SDS Sheet            | LED_Lamp   |