SATCO NUVO

Project Name

ocation Prepared By



SATCO S11954

22T8/LED/60-850/BP

Notes

w1 10-27-2025 05:20

Status	Active	
Watts	22W	
Incandescent Equivalent	40W	
Fluorescent Equivalent	58W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	60	
Finish	Frost	
CCT (Kelvin)	5000K	
Temperature	Natural Light	
CRI	80+	
Lumens	2800L	
Beam Spread	160	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	60
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.77

Additional Information	
Shatter-Proof Type	PET Coated
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp