

Project Name

Location

Prepared By



# SATCO S11954

22T8/LED/60-850/BP

Notes

[www] 01-15-2024 02:40:00

## General

Status	Active
Watts	22W
Incandescent Equivalent	40W
Fluorescent Equivalent	58W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	60
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	83
Lumens	2800L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

## Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)

## Physical

MOL	60
MOD	1
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.448

## Additional Information

Shatter-Proof Type	PET Coated
Tube Guard Use	Yes
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

## Compliance

Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

