

Project Name

Location

Prepared By



# SATCO S11958

24T8/LED/96-840/BP/FA8

## Notes

(www) 08-05-2023 23:44:01

### General

Status	Active
Watts	24W
Incandescent Equivalent	100W
Fluorescent Equivalent	59W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	3500L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

### Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

### Physical

MOL	93.88
MOD	1
Material	Glass
Lens Finish	White
Housing Color	White
Weight (lb.)	0.88

### Additional Information

Additional Info	Suitable for Emergency Lighting only with Satco EM Driver #S8002
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

### Compliance

Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLO7K8JCRGBZ
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp