

Project Name

ocation Prepared By



SATCO S11964

18T8/LED/48-840/BP/R17D/HO

Notes

Status	Active
Watts	18W
Incandescent Equivalent	90W
Fluorescent Equivalent	63W
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	48
Finish	White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2500L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	46
MOD	1.1
Material	Glass
Lens Finish	White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.58

Additional Information	
Shatter-Proof Type	PET Coated
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance		
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component	
Location Rating	Damp	
DLC Approved	No	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
SDS Sheet	LED_Lamp	