

Project Name

Location

Prepared By



SATCO S11967

30T8/LED/72-865/BP/R17D/HO

Notes

[www] 03-28-2023 09:13:27

General

Status	Active
Watts	30W
Incandescent Equivalent	125W
Fluorescent Equivalent	87W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	72
Finish	White
CCT (Kelvin)	6500K
Temperature	Daylight
CRI	80+
Lumens	4200L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	70
MOD	1.1
Material	Glass
Lens Finish	White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.81

Additional Information

Shatter-Proof Type	PET Coated
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp