SATCO NUVO

Project Name

ocation Prepared By



SATCO S11971

13T8U6/LED/22.5-835/DUAL

Notes

rw] 10-27-2025 05:2

Status	Discontinued	
Substitute	S18413	
Watts	13W	
Incandescent Equivalent	50W	
Fluorescent Equivalent	32W	
Volts	120V-277V	
Ballast Type	Type A/B	
Shape	T8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	22.5	
Finish	Frost	
CCT (Kelvin)	3500K	
Temperature	Neutral White	
CRI	80+	
Lumens	1950L	
Beam Spread	160	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	U-Bend	
Technology	LED	

Electrical		
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)	
Operating Frequency	50/60Hz	
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility	
Power Factor	0.9	
THD	20%	
Operating Temperature	-25C (-13F) to +45C (+113F)	

Physical	
MOL	22.59
MOD	1.1
Leg Spacing	6
Material	Plastic
Lens Finish	Frost
Lens Material	Plastic (PS)
Housing Color	White
Weight (lb.)	0.77

Additional Information		
Shatter-Proof Type	Yes	
Tube Guard Use	Yes	
Installation Notes	Not for use in vapor tight fixtures. Direct replacement for 32W/23T8/U6 lamps only	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	PLD6LILX58CD	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	ETL Sanitation listed (conforms to NSF)	
SDS Sheet	LED_Lamp	