SATCO NUVO

Project Name

Location Prepared By



SATCO S11972

13T8U6/LED/22.5-840/DUAL

Notes

ww] 10-27-2025 05:2

	Discontinued
ubstitute	
	S18413
/atts	13W
ncandescent Equivalent	50W
luorescent Equivalent	32W
olts	120V-277V
allast Type	Type A/B
hape	T8
ase	Medium Bi Pin
NSI Base	G13
ominal Length	22.5
inish	Frost
CT (Kelvin)	4000K
emperature	Cool White
RI	80+
umens	2000L
eam Spread	160
immable	Yes-Dimmable
ours Rated	50000
roduct Category	U-Bend
echnology	LED

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	22.59
MOD	1.1
Leg Spacing	6
Material	Plastic
Lens Finish	Frost
Lens Material	Plastic (PS)
Housing Color	White
Weight (lb.)	0.77

Additional Information		
Shatter-Proof Type	Yes	
Tube Guard Use	Yes	
Installation Notes	Not for use in vapor tight fixtures. Direct replacement for 32W/23T8/U6 lamps only	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLX80LFIAOD6
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)
SDS Sheet	LED_Lamp