

Project Name

ocation Prepared By



SATCO S11974

12T8/LED/48-830/DM/A-B

Notes

Status	Active	
Watts	12W	
Incandescent Equivalent	50W	
Fluorescent Equivalent	32W	
Volts	120V-277V	
Ballast Type	Type A/B	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Frost	
CCT (Kelvin)	3000K	
Temperature	Warm White	
CRI	80+	
Lumens	1700L	
Beam Spread	210	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical		
MOL	48	
MOD	1	
Lens Finish	Frost	
Lens Material	Glass	
Housing Color	White	
Weight (lb.)	0.48	

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-8MP0V3
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp