

Notes

General	
Status	Active
Watts	10.5W
Incandescent Equivalent	50W
Fluorescent Equivalent	25W/28W/32W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	1650L
Beam Spread	180
Hours Rated	70000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
THD	20%
Physical	
MOL	47.78
MOD	1
Material	Plastic
Lens Finish	Frost
Lens Material	Plastic
Housing Color	White
Additional Information	
Installation Notes	Not for use in vapor tight fixtures
Warranty	Not for use in vapor tight fixtures. 5-Years
Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-PE2TIM
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

