

Project Name

Location

Prepared By



SATCO S11983

9T8/LED/24-850/BP/USA

Notes

(www) 18-12-2023 09:20:07

General	
Status	Discontinued
Watts	9W
Incandescent Equivalent	40W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1150L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	23.78
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.24

Additional Information	
Installation Notes	Not for use in vapor tight fixtures.
Specification Note	Compatible with S8000 and S8002 LED EM Driver
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLL16UMVG8VL
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp