



Notes

12T8/LED/36-835/BP/USA

w] 07-09-2025 00:

Status	Discontinued	
Watts	12W	
Incandescent Equivalent	50W	
Fluorescent Equivalent	25W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	36	
Finish	Frost	
CCT (Kelvin)	3500K	
Temperature	Neutral White	
CRI	80+	
Lumens	1400L	
Beam Spread	210	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	35.78
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.33

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Specification Note	Compatible with S8000 and S8002 LED EM Driver	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLF16HQKCCVD
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp