

Project Name

ocation Prepared By



Notes

w] 08-10-2025 22:4

Status	Discontinued
Watts	10.5W
Incandescent Equivalent	50W
Fluorescent Equivalent	30W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1700L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	47.78
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.44

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Specification Note	Compatible with S8000 and S8002 LED EM Driver	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLFF68VB1ET4
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp