Project Name

Prepared By



SATCO S12112 6.5G40/SW/LED/E26/27K/120V

Notes

General	
Status	Discontinued
Substitute	S21255
Watts	6.5W
Incandescent Equivalent	60W
Volts	120V
Shape	G40
Base	Medium
ANSI Base	E26
Finish	Soft White
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	650L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Globe
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	50-60Hz
Power Factor	>0.7
Power Factor	
	>0.7
Power Factor Operating Position Operating Temperature	>0.7 Universal
Power Factor Operating Position Operating Temperature Physical	>0.7 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5
Power Factor Operating Position Operating Temperature Physical MOL MOD	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91
Power Factor Operating Position Operating Temperature Physical MOL	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5
Power Factor Operating Position Operating Temperature Physical MOL MOD	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.)	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp Non-Compliant Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp Non-Compliant Non-Compliant Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp Non-Compliant Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp Non-Compliant Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years cULus Damp Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	>0.7 Universal -20C (-4F) to +45C (+113F) 6.5 4.91 0.21 Yes 2-Years CULus Damp Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale

