SATCO NUVO

Project Name

ocation

Prepared By



4B11/LED/930/CL/E12/10PK

Notes

General	
Status	Active
Watts	4W
Incandescent Equivalent	40W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	3000K
Temperature	Soft White
CRI	92
Lumens	350L
Beam Spread	300
Dimmable	Yes-Dimmable
Dimming Note	120V Only
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
	60Hz
Electrical Operating Frequency Power Factor	60Hz 0.7
Operating Frequency	
Operating Frequency Power Factor	0.7
Operating Frequency Power Factor Operating Temperature Physical	0.7 -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Temperature	0.7
Operating Frequency Power Factor Operating Temperature Physical MOL MOD	0.7 -20C (-4F) to +45C (+113F) 3.97
Operating Frequency Power Factor Operating Temperature Physical MOL	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet Lawful for sale in California
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet Lawful for sale in California Lawful for sale
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status IP Rating	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet Lawful for sale in California Lawful for sale IP65
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status IP Rating ROHS Compliant	0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet Lawful for sale in California Lawful for sale IP65 Yes