SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	4W
Incandescent Equivalent	40W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	3000K
Temperature	Soft White
CRI	92
Lumens	350L
Beam Spread	300
Dimmable	Yes-Dimmable
Dimming Note	120V Only
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Integrated Camera Electrical	No
Electrical	No 60Hz
_	
Electrical Operating Frequency	60Hz
Electrical Operating Frequency Power Factor	60Hz 0.7
Electrical Operating Frequency Power Factor Operating Temperature Physical	60Hz 0.7 -20C (-4F) to +45C (+113F)
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet Lawful for sale in California
Electrical Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	60Hz 0.7 -20C (-4F) to +45C (+113F) 3.97 1.38 None 0.03 Yes 2-Years CULus - Listed Wet Lawful for sale in California Lawful for sale



