SATCO NUVO

Project Name

Location

Prepared By



Notes

ww] 01-15-2024 02:40

General	
Status	Discontinued
Substitute	S13163
Watts	35W
Incandescent Equivalent	300W
HID Equivalent	150W
Volts	100V-277V
Shape	A25
Base	Mogul Extended
ANSI Base	EX39
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	4830L
Beam Spread	280
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Type A
Technology	LED
Min Compartment Size	Diameter: 6 in. Height: 8.5 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Power Factor	>0.9
	-
Operating Position	Universal
Operating Position Operating Temperature	Universal -25C (-13F) to +45C (+113F)
Operating Temperature	
Operating Temperature Physical	-25C (-13F) to +45C (+113F)
Operating Temperature Physical MOL	-25C (-13F) to +45C (+113F) 7.25
Operating Temperature Physical MOL MOD	-25C (-13F) to +45C (+113F) 7.25 3.75
Operating Temperature Physical MOL MOD Lens Finish	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost
Operating Temperature Physical MOL MOD Lens Finish Lens Material	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS)
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White
Operating Temperature Physical MOL MOD Lens Finish Lens Material	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS)
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro CULus - Listed Damp
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro cULus - Listed Damp No
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro cULus - Listed Damp No No
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro cULus - Listed Damp No No No Exempt - >2600 Lumens
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro CULus - Listed Damp No No Exempt - >2600 Lumens Lawful for sale in California
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro CULus - Listed Damp No No Exempt - >2600 Lumens Lawful for sale in California Lawful for sale
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status Colorado Status	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro cULus - Listed Damp No No No Exempt - >2600 Lumens Lawful for sale Lawful for sale Lawful for sale
Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status Colorado Status Hawaii Status	-25C (-13F) to +45C (+113F) 7.25 3.75 Frost Plastic (PS) White 1.57 Yes 5 Year Limited - Hi-Pro CULus - Listed Damp No No Ro Exempt - >2600 Lumens Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale

Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



