

Project Name

Location

Prepared By



SATCO S13112

80W/LED/HID-HB/4K/120-277V

Notes

(revised) 07-07-2023 00:13:04

General

Status	Discontinued
Substitute	S33112
Watts	80W
Incandescent Equivalent	400W
HID Equivalent	250W
Volts	120V-277V
Shape	HB60
Base	Mogul Extended
ANSI Base	EX39
Finish	Translucent White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	10000L
Beam Spread	115
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Hi-Bay
Technology	LED
Min Compartment Size	Length: 13.5 in. Width: 13.5 in. Height: 12 in.
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	50-60Hz
Candlepower	3000
Power Factor	0.98/0.92
Operating Position	Universal
Surge Protection	Built-in surge protection - 6KV
Operating Temperature	-40C (-40F) to +60C (+140F)

Physical

MOL	10.12
MOD	7.48
Lens Finish	Translucent White
Housing Color	White
Weight (lb.)	1.72

Additional Information

Rated For Enclosed Fixture	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp