

Project Name

Location

Prepared By



SATCO S13130

16W/LED/HID/ED23/850/E26

Notes

[www] 03-28-2023 09:13:09

General

Status	Active
Substitute	S13182
Watts	16W
Incandescent Equivalent	125W
Fluorescent Equivalent	32W
HID Equivalent	70W
Volts	120V-277V
Shape	ED23
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	2000L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	25000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Operating Temperature	-30C (-22F) to +65C (+149F)

Physical

MOL	7.28
MOD	2.95
Lens Finish	White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.25

Additional Information

Additional Info	HI-PRO Filament 120-277V
Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	3 Year Limited - 12 hr per day

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC Approved	No
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp