SATCO NUVO

Project Name

Location Prepared By



Notes

General	
Status	Active
Substitute	S13185
Watts	313163 30W
Incandescent Equivalent	200W
Fluorescent Equivalent	65W
HID Equivalent	125W
Volts	120V-277V
Shape	ED23
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	4000L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	25000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass
Electrical	,,
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Operating Position Operating Temperature	-30C (-22F) to +65C (+149F)
Operating Temperature	
Operating Temperature Physical	-30C (-22F) to +65C (+149F)
Operating Temperature Physical MOL	-30C (-22F) to +65C (+149F) 7.68
Operating Temperature Physical MOL MOD	-30C (-22F) to +65C (+149F) 7.68 2.95
Operating Temperature Physical MOL MOD Lens Finish	-30C (-22F) to +65C (+149F) 7.68 2.95 White
Operating Temperature Physical MOL MOD Lens Finish Lens Material	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures.
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures.
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day cULus - Listed
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day cULus - Listed Wet
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus - Listed Wet No
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day cULus - Listed Wet No No
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day cULus - Listed Wet No No Exempt - >2600 Lumens
Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	-30C (-22F) to +65C (+149F) 7.68 2.95 White Glass White 0.31 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus - Listed Wet No No Exempt - >2600 Lumens Lawful for sale in California

Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



