

Project Name

Location

Prepared By



## SATCO S13154

152W/LED/HID-HB/840/120-277V

### Notes

1www|10-27-2025 05:20:07

### General

Status	Discontinued
Watts	152W
Incandescent Equivalent	1000W
Fluorescent Equivalent	250W
HID Equivalent	750W
Volts	120V-277V
Shape	HB64
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	25000L
Beam Spread	180
Hours Rated	50000
Product Category	Hi-Bay Flood
Technology	LED
Min Compartment Size	Diameter: 19.69 in. Height: 19.69 in.
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50/60Hz
Power Factor	0.9
Operating Position	Base Up
Surge Protection	Built-in surge protection - 6KV
THD	20%
Operating Temperature	-40C (-40F) to +60C (+140F)

### Physical

MOL	9.33
MOD	7.91
Lens Finish	Clear
Lens Material	Glass
Housing Color	White
Weight (lb.)	3.3

### Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP40
Installation Notes	Not for use in vapor tight fixtures. Vertical Only with base up
Warranty	5-Years

### Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PNUQ2VIP
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp