SATCO NUVO

Project Name

Location

Prepared By



Notes

www] 05-15-2024 04:42:

Energy Star

General	
Status	Active
Watts	35W/17W
Incandescent Equivalent	300W
Fluorescent Equivalent	85W
HID Equivalent	100W-175W
Volts	100V-277V
Shape	AP28
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	4550L/2380L
Beam Spread	280
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Type A
Technology	LED
Min Compartment Size	Length: 6 in. Width: 6 in. Height:
	8.5 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage
Dimming Note	selection switch on lamp
Power Factor	selection switch on lamp
Power Factor	>0.9
Power Factor Operating Position	>0.9 Universal
Power Factor Operating Position Surge Protection	>0.9 Universal Built-in surge protection - 2.5KV
Power Factor Operating Position Surge Protection Operating Temperature	>0.9 Universal Built-in surge protection - 2.5KV
Power Factor Operating Position Surge Protection Operating Temperature Physical	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11 Yes IP64 Lumen/Watt/CCT Ratio Chart in
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents.
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note Installation Notes	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents. Not for use in vapor tight fixtures.
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note Installation Notes Warranty Compliance	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents. Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Notes Warranty	>0.9 Universal Built-in surge protection - 2.5KV -22C (-30F) to +45C (+113F) 6.26 3.39 Frost Polycarbonate (PC) White 1.11 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents. Not for use in vapor tight fixtures.

No

DLC Approved	No
CA T20 / T24 Rationale	Exempt - >2600 Lumens
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



