SATCO NUVO

Project Name

ocation Prepared By



SATCO S13163

35W/AP28/LED/CCT/100-277V/EX39

Notes

| Status | Active |
|-------------------------|--|
| Watts | 35W/17W |
| Incandescent Equivalent | 300W |
| Fluorescent Equivalent | 85W |
| HID Equivalent | 100W-175W |
| Volts | 120V-277V |
| Shape | AP28 |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | White |
| CCT (Kelvin) | 3000K/4000K/5000K |
| Temperature | Warm to Cool White |
| CRI | 80+ |
| Lumens | 4550L/2380L |
| Beam Spread | 280 |
| Hours Rated | 50000 |
| Product Category | Туре А |
| Technology | LED |
| Min Compartment Size | Length: 6 in. Width: 6 in. Height: 8.5 in. |
| Ballasting Requirements | Ballast Bypass |

| 50/60Hz |
|-----------------------------------|
| Step Dimming |
| >0.9 |
| Universal |
| Built-in surge protection - 2.5KV |
| 15% |
| -22C (-30F) to +45C (+113F) |
| |

| Physical | |
|---------------|--------------------|
| MOL | 6.54 |
| MOD | 3.39 |
| Lens Finish | Frost |
| Lens Material | Polycarbonate (PC) |
| Housing Color | White |
| Weight (lb.) | 0.94 |

| Additional Information | | |
|----------------------------|--|--|
| Rated For Enclosed Fixture | Yes | |
| IP Rating | IP64 | |
| Specification Note | Lumen/Watt/CCT Ratio Chart in Documents. | |
| Installation Notes | Not for use in vapor tight fixtures. | |
| Warranty | 5-Years | |

| Compliance | |
|----------------------|--|
| Safety Listing | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | S-B1AY6N |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED Lamp |