SATCO NUVO

Project Name

ocation

Prepared By



SATCO S13164

45W/AP32/LED/CCT/100-277V/E26

Notes

ww1 10-27-2025 05:20:

General	
Status	Active
Watts	45W/22W
Incandescent Equivalent	300W
Fluorescent Equivalent	100W
HID Equivalent	150W-175W
Volts	120V-277V
Shape	AP32
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	5850L/3060L
Beam Spread	280
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Type A
Technology	LED
Min Compartment Size	Length: 6 in. Width: 6 in. Height: 8.5 in.
Ballasting Requirements	Ballast Bypass
Electrical	

Electrical		
Operating Frequency	50/60Hz	
Dimming Type	Reverse Phase	
Dimming Note	Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.	
Power Factor	>0.9	
Operating Position	Universal	
Surge Protection	Built-in surge protection - 3KV	
Operating Temperature	-22C (-30F) to +45C (+113F)	

Physical		
MOL	7.05	
MOD	3.9	
Lens Finish	Frost	
Lens Material	Polycarbonate (PC)	
Housing Color	White	
Weight (lb.)	1.69	

Additional Information	
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	Lumen/Watt/CCT Ratio Chart in Documents.
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

