SATCO NUVO

Project Name

ocation Prepared By



Notes

rw1 12-22-2024 23:1

Status	Active	
Watts	13.5W	
HID Equivalent	50W	
Volts	120V-277V	
Shape	ED17	
Base	Medium	
ANSI Base	E26	
Finish	Clear	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80	
Lumens	2000L	
Beam Spread	320	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	LED HID	
Technology	LED	
Min Compartment Size	Size Length: 5.98 in. Width: 5.98 in. Height: 1 in.	
allasting Requirements Ballast Bypass		
Electrical		
Operating Frequency	60Hz	
Power Factor	0.9	
Operating Position	Universal	
Surge Protection	Built-in surge protection - 4KV	
Operating Temperature	-30C (-22F) to +65C (+149F)	
Physical		
MOL	5.8	
MOD	2.13	
Weight (lb.)	0.25	

Additional Information		
Rated For Enclosed Fixture	Yes	
IP Rating	IP65	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5 Year Limited - Hi-Pro	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC Approved	No
CA T20 / T24 Rationale	Non-Compliant - <82 CRI
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
RoHS Compliant	Yes
FCC Compliant	Yes