## SATCO NUVO

Project Name

ocation Prepared By



Notes

wl 08-10-2025 22:40:

Status	Active
Watts	40W
HID Equivalent	200W
Volts	120V-277V
Shape	ED37
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	7500L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 17.83 in. Width: 17.83 in. Height: 13.39 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV

Operating Temperature	-30C (-22F) to +65C (+149F)
Physical	
MOL	10.3
MOD	4.7
Housing Color	None
Weight (lb.)	0.64

Additional Information		
Rated For Enclosed Fixture	Yes	
IP Rating	IP65	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC Approved	Yes
DLC ID	S-8517W5
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp