SATCO NUVO

Project Name

ocation Prepared By



Notes

w1 12-22-2024 23:10

General	
Status	Active
Watts	45W
HID Equivalent	250W
Volts	120V-277V
Shape	ED37
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	7500L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 17.83 in. Width: 17.83 in. Height: 13.39 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)
Physical	
MOL	10.3
MOD	4.7
Weight (lb.)	0.99
Additional Information	
Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC ID	FALSE
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes