

Project Name

Location

Prepared By



SATCO S13195

25W/LED/HID/ED28/CCT/EX39/CL

Notes

1www|10-27-2025 05:20:50

General

| | |
|-------------------------|---|
| Status | Active |
| Watts | 17W/20.5W/25W |
| HID Equivalent | 50W/70W/100W |
| Volts | 120V-277V |
| Shape | ED28 |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | Clear |
| CCT (Kelvin) | 3000K/4000K/5000K |
| Temperature | Soft White to Natural Light |
| CRI | 80+ |
| Lumens | 3100L/3700L/4500L |
| Beam Spread | 360 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Product Category | LED HID |
| Technology | LED |
| Min Compartment Size | Length: 14.02 in. Width: 8.03 in. Height: 8.03 in. |
| Ballasting Requirements | Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required |

Electrical

| | |
|-----------------------|--|
| Operating Frequency | 50/60Hz |
| Candlepower | 250 |
| Dimming Type | Step Dimming |
| Dimming Note | Only dimmable through wattage selection switch on lamp |
| Power Factor | >0.9 |
| Operating Position | Universal |
| Surge Protection | Built-in surge protection - 2KV |
| THD | <20% |
| Operating Temperature | -30C (-22F) to +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 9.92 |
| MOD | 3.58 |
| Housing Color | White |
| Weight (lb.) | 0.55 |

Additional Information

| | |
|----------------------------|--------------------------------------|
| Rated For Enclosed Fixture | Yes |
| Installation Notes | Not for use in vapor tight fixtures. |
| Warranty | 5-Years |

Compliance

| | |
|----------------------|-------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Wet |
| DLC Approved | Yes |
| DLC ID | S-YZF3TT |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |