

Project Name

Location

Prepared By



# SATCO S16400

9T8/LED/HO-SIGN/24-840/BP

**Notes**

[www] 16-11-2021 02:00:30

**General**

Status	Active
Watts	9W
Fluorescent Equivalent	37W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	24
Finish	Frost
CCT (Kelvin)	4000
Temperature	Cool White
CRI	83
Lumens	1200L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-30C (-22F) to a maximum of +45C (+113F)

**Physical**

MOL	21.88
MOD	1
Material	Plastic
Lens Finish	Frost

**Additional Information**

Installation Notes	No ballast or external driver required; Direct wire 120-277V line voltage.
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass - Outdoor Sign

**Compliance**

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes