

Project Name

Location

Prepared By



SATCO S18405

4.5W/LED/CFL/5CCT/G23/BP

Notes

[www] 10-27-2025 05:20:50

General

Status	Active
Watts	4.5W
Fluorescent Equivalent	5W/7W/9W
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	G23 (2-Pin)
ANSI Base	G23
Finish	Frost
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Temperature	Warm White to Natural Light
CRI	80+
Lumens	450L/475L/500L/500L/475L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	6.5
MOD	1.27
Housing Color	White
Weight (lb.)	0.09

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cETLus - Classified
Location Rating	Damp
DLC Approved	No
NSF Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp