## SATCO NUVO

Project Name

ocation Prepared By



Notes

w] 10-27-2025 05:20

Status	Active
Vatts	11.5W/13W/15W
ncandescent Equivalent	50W
luorescent Equivalent	32W
olts/	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
NSI Base	G13
inish	Frost
CT (Kelvin)	3000K/3500K/4000K/5000K/6500K
emperature	Soft White to Daylight
RI	80+
umens	1800L/2000L/2200L
eam Spread	210
Dimmable	Yes-Dimmable
lours Rated	50000
roduct Category	U-Bend
echnology	LED

Electrical		
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)	
Operating Frequency	50/60Hz	
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility	
Power Factor	>0.9	
THD	<20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	22.43
MOD	0.96
Leg Spacing	5.98
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.55

Additional Information	
Installation Notes	Not for use in vapor tight fixtures. Direct replacement for 32W T8 U6 lamps only.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	S-GDKRYT	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
SDS Sheet	LED_Lamp	