

Project Name

Location

Prepared By



Notes

[\[www\] 18-12-0025 01-20-07](#)

General	
Status	Active
Watts	11.5W/13W/15W
Incandescent Equivalent	50W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	1800L/2000L/2200L
Beam Spread	210
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	U-Bend
Technology	LED

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	22.43
MOD	0.96
Leg Spacing	5.98
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.55

Additional Information	
Installation Notes	Not for use in vapor tight fixtures. Direct replacement for 32W T8 U6 lamps only.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-GDKRYT
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp