



Notes

16PLL/LED/5CCT/BP

Status	Active
Watts	16W
Fluorescent Equivalent	36W
Volts	120V-277V
Ballast Type	Туре В
Shape	T5
Base	2G11
ANSI Base	2G11
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
emperature	Soft White to Daylight
CRI	80+
umens	1900L/1950L/2000L/2000L/2000L
Beam Spread	115
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Universal
rechnology rechnology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	

Physical	
MOL	16.4
MOD	1.72
Housing Color	White
Weight (lb.)	0.28

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component	
Location Rating	Damp	
DLC Approved	No	
NSF Approved	Yes	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED_Lamp	