

Project Name

Location

Prepared By



SATCO S19947

11T5/LED/24-840/DR

Notes

(review) 18-12-2023 05:20:07

General

| | |
|-------------------------|-------------------|
| Status | Active |
| Watts | 11W |
| Incandescent Equivalent | 50W |
| Fluorescent Equivalent | 24W |
| Volts | Ballast Dependent |
| Ballast Type | Type A |
| Shape | T5 |
| Base | Miniature Bi Pin |
| ANSI Base | G5 |
| Nominal Length | 24 |
| Finish | White |
| CCT (Kelvin) | 4000K |
| Temperature | Cool White |
| CRI | 80+ |
| Lumens | 1400L |
| Beam Spread | 185 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Product Category | Type A |
| Technology | LED |

Electrical

| | |
|-------------------------|---|
| Ballasting Requirements | Ballast required, check compatibility |
| Operating Frequency | 50/60Hz |
| Dimming Note | Only in Type A mode; Check Ballast MFG for Dimmer Compatibility |
| Power Factor | 0.9 |
| THD | 20% |
| Operating Temperature | -20C (-4F) to +45C (+113F) |

Physical

| | |
|---------------|------------------|
| MOL | 22.5 |
| MOD | 0.63 |
| Material | Aluminum / Glass |
| Lens Material | Glass |
| Housing Color | None |
| Weight (lb.) | 0.13 |

Additional Information

| | |
|----------------------------|---|
| Additional Info | Light Emitting Area of 325 degrees; System Wattage (Type A) - 14W |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5-Years |

Compliance

| | |
|----------------------|-----------------------------------|
| Safety Listing | cULus - Certified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |