SATCO NUVO

Project Name

Location

Prepared By



SATCO S21330 58T15/CL/LED/927/120V

Notes

Watts5Incandescent Equivalent4Volts1ShapeBBaseMANSI BaseEFinishCCCT (Kelvin)2TemperatureWCRI9Lumens4Beam Spread3DimmableYDimming Note1Hours Rated1Product CategoryB	Active W 00W 20V 20T15 Addium 226 210 200
Watts5Incandescent Equivalent4Volts1ShapeBBaseMANSI BaseEFinishCCCT (Kelvin)2TemperatureWCRI9Lumens4Beam Spread3DimmableYDimming Note1Hours Rated1Product CategoryB	W 0W 20V 20V 21T15 Aedium 226 200 200 200 200 200 200 200 200 200
Volts1ShapeBBaseMANSI BaseEFinishCCCT (Kelvin)2TemperatureWCRI9Lumens4Beam Spread3DimmableYDimming Note1Hours Rated1Product CategoryB	20V 5T15 4edium 226 200 200 200 200 200 200 200 200 200
Shape B Base M ANSI Base E Finish C CCT (Kelvin) 2 Temperature W CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	ST15 Aedium 226 Clear 700K Varm White 10+ 550L 600 res-Dimmable 20V only 55000 ST
Base M ANSI Base E Finish C CCT (Kelvin) 2 Temperature W CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	Medium 126 128 129 1200K Varm White 100+ 150L 160 160 160 161 162 163 164 165 164 165 165 164 165 165 166 167 168 168 169 169 169 160 160 160 160 160 160 161 162 163 164 165 165 166 167 168 168 169 169 169 160 160 160 160 160 <t< td=""></t<>
ANSI Base E Finish C CCT (Kelvin) 2 Temperature W CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	226 21ear 2700K Varm White 10+ 150L
Finish C CCT (Kelvin) 2 Temperature W CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	Clear Clear Cloar Varm White 00+ 550L 00 Ces-Dimmable 20V only 5500 5000 ST
CCT (Kelvin) 2 Temperature W CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category 8	700K Varm White 0+ 550L 600 (es-Dimmable 20V only 5000
Temperature W CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	Varm White 10+ 150L 100 100 100 100 100 100 100 1
CRI 9 Lumens 4 Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	0+ 50L :00 :es-Dimmable :20V only :5000 :T
Lumens 4 Beam Spread 3 Dimmable Yr Dimming Note 1 Hours Rated 1 Product Category B	50L 600 (es-Dimmable 20V only 5000 ST
Beam Spread 3 Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	00 'es-Dimmable 20V only 5000 IT
Dimmable Y Dimming Note 1 Hours Rated 1 Product Category B	res-Dimmable 20V only 5000 IT
Dimming Note 1 Hours Rated 1 Product Category B	20V only 5000 IT
Hours Rated 1 Product Category B	5000 3T
Product Category B	T
Technology	ED
Electrical	
Operating Frequency 6	i0Hz
Power Factor 0	0.76
Operating Temperature -2	20C (-4F) to +45C (+113F)
Physical	
MOL 4	.06
MOD 1	81
Housing Color N	lone
Weight (lb.)	.055
Additional Information	
Rated For Enclosed Fixture Y	Yes
Warranty 2	-Years
Compliance	
Safety Listing cl	ULus - Certified; cULus - Listed
	Vet
	ilament LED Lamp
NSF Approved N	lo
California Status	awful for sale in California
Title 20 / 24 Status	awful for sale
RoHS Compliant Y	es
FCC Compliant Y	es
Canadian Standard ICES-005 C	Class B
SDS Sheet	ED_Lamp

