## SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	4W
Incandescent Equivalent	40W
Volts	120V
Shape	T6.5
Base	Bayonet Double Contact
ANSI Base	BA15d
Finish	Frost
CCT (Kelvin)	3000K
Temperature	Soft White
CRI	90+
Lumens	360L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Tubular
Technology	LED
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz >0.7
Power Factor	>0.7
Power Factor Operating Temperature	>0.7
Power Factor Operating Temperature Physical	>0.7 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	>0.7 -20C (-4F) to +45C (+113F) 5.12
Power Factor Operating Temperature  Physical  MOL  MOD	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79
Power Factor Operating Temperature Physical MOL MOD Housing Color	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture Installation Notes	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures.
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture Installation Notes  Warranty	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures.
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture Installation Notes  Warranty  Compliance	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures. 2-Years
Power Factor Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Installation Notes Warranty  Compliance Safety Listing	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures. 2-Years  cRUus - Recognized Component
Power Factor Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Installation Notes Warranty  Compliance Safety Listing Location Rating	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures. 2-Years  cRUus - Recognized Component Wet
Power Factor Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Installation Notes Warranty  Compliance Safety Listing Location Rating UL Application	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures. 2-Years  cRUus - Recognized Component Wet Filament LED Lamp
Power Factor Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture Installation Notes  Warranty  Compliance  Safety Listing Location Rating UL Application California Status	>0.7 -20C (-4F) to +45C (+113F)  5.12 0.79 Frost 0.05  Yes Not for use in vapor tight fixtures. 2-Years  cRUus - Recognized Component Wet Filament LED Lamp Lawful for sale in California

