

Project Name

Location

Prepared By



SATCO S21407

PLT/16W/V/LED/850/4P/DR

Notes

[www] 03-28-2023 09:13:27

General

Status	Discontinued
Substitute	S21412
Watts	16W
Fluorescent Equivalent	42W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	PL
Base	G24q (4-Pin)
ANSI Base	G24q
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1850L
Beam Spread	110
Hours Rated	50000
Product Category	PL
Operating Position	Base Up or Down
Technology	LED

Electrical

Ballasting Requirements	Ballast required
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	5.19
MOD	3.75
Housing Color	White
Weight (lb.)	0.35

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus
Location Rating	Damp
DLC Approved	Yes
DLC ID	PL9E574BZGHJ
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Yes
SDS Sheet	LED_Lamp