SATCO NUVO

Project Name

ocation Prepared By



Notes

wl 10-21-2025 23:30:

Status	Active
Watts	9W
Fluorescent Equivalent	26W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	G24q-4 (4-Pin)
ANSI Base	G24q-4
Finish	White
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Temperature	Warm White to Natural Light
CRI	80+
Lumens	1100L
Beam Spread	120
Hours Rated	50000
Product Category	PL 4-Pin
Operating Position	Universal
Technology	LED

Electrical		
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)	
Operating Frequency	50/60Hz	
Dimming Note	Only Dimmable with Compatible Dimming Ballasts	
Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	6.76
MOD	2.36
Housing Color	White
Weight (lb.)	0.4

Additional Information		
Installation Notes	Suggested wattage equivalency = 26W CFL	
Rated For Enclosed Fixture	No	
Warranty	5-Years	

Compliance		
Safety Listing CULus - Certified; cULus - Classifie Listed		
Location Rating	Damp	
DLC Approved	No	
NSF Approved	Yes	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	I FD Lamp	