SATCO NUVO

Project Name

ocation Prepared By



Notes

rw] 10-27-2025 05:20

Status	Active
Watts	16W
Fluorescent Equivalent	42W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	G24q-4 (4-Pin)
ANSI Base	G24q-4
Finish	White
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Геmperature	Warm White to Natural Light
CRI	80+
Lumens	1850L
Beam Spread	120
Hours Rated	50000
Product Category	PL 4-Pin
Operating Position	Universal
Technology	LED

Electrical		
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)	
Operating Frequency	50/60Hz	
Dimming Note	Only Dimmable with Compatible Dimming Ballasts	
Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	6.76
MOD	2.36
Housing Color	White
Weight (lb.)	0.4

Additional Information	
Installation Notes	Suggested wattage equivalency = 42W CFL
Rated For Enclosed Fixture	No
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp