

Project Name

Location

Prepared By



SATCO S21415

22W/PL/LED/HL/5CCT/G24

Notes

(www) 03-28-2023 09:13:09

General

Status	Active
Watts	22W
Fluorescent Equivalent	42W
Volts	120V/277V
Ballast Type	Type B
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	White
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Warm White to Natural Light
CRI	80+
Lumens	2750L-2860L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL 2-Pin
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Operating Frequency	50/60Hz
Power Factor	>0.9
THD	20%
Operating Temperature	-25C (-13F) to +50C (+122F)

Physical

MOL	6.38
MOD	1.95
Housing Color	White
Weight (lb.)	0.43

Additional Information

Installation Notes	Suggested wattage equivalency = 42W CFL
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp