## SATCO NUVO

Project Name

Prepared By



2.5W CTC/LED/27K/CL/120V/2CD

Notes

General	
Status	Discontinued
Substitute	S21817
Watts	2.5W
Incandescent Equivalent	25W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	180L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Power Factor	1
Power Factor Operating Position	1 Universal
Operating Position	Universal
Operating Position Operating Temperature	Universal
Operating Position Operating Temperature Physical	Universal -20C (-4F) to +45C (+113F)
Operating Position Operating Temperature Physical MOL	Universal -20C (-4F) to +45C (+113F) 3.88
Operating Position Operating Temperature Physical MOL MOD	Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years cULus - Certified; cULus - Listed Damp Non-Compliant
Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant
Operating Position         Operating Temperature         Physical         MOL         MOD         Weight (Ib.)         Additional Information         Rated For Enclosed Fixture         Warranty         Compliance         Safety Listing         Location Rating         California Status         Title 20 / 24 Status         Colorado Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale
Operating Position         Operating Temperature         Physical         MOL         MOD         Weight (Ib.)         Additional Information         Rated For Enclosed Fixture         Warranty         Compliance         Safety Listing         Location Rating         California Status         Title 20 / 24 Status         Colorado Status         Hawaii Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale
Operating Position         Operating Temperature         Physical         MOL         MOD         Weight (Ib.)         Additional Information         Rated For Enclosed Fixture         Warranty         Compliance         Safety Listing         Location Rating         California Status         Title 20 / 24 Status         Colorado Status         Hawaii Status         Nevada Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale
Operating Position         Operating Temperature         Physical         MOL         MOD         Weight (Ib.)         Additional Information         Rated For Enclosed Fixture         Warranty         Compliance         Safety Listing         Location Rating         California Status         Title 20 / 24 Status         Colorado Status         Hawaii Status         Nevada Status         Vermont Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Position         Operating Temperature         Physical         MOL         MOD         Weight (Ib.)         Additional Information         Rated For Enclosed Fixture         Warranty         Compliance         Safety Listing         Location Rating         California Status         Title 20 / 24 Status         Colorado Status         Hawaii Status         Nevada Status         Vermont Status         Washington Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale

Copyright 2023 Satco Products, Inc. All Rights Reserved

