SATCO NUVO

Project Name

ocation Prepared By



Notes

v1 08-05-2025 22:44:01

General	
Status	Discontinued
Substitute	S21819
Watts	4.5W
Incandescent Equivalent	40W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	350L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Power Factor	1
Power Factor Operating Position	1 Universal
Operating Position	Universal
Operating Position Operating Temperature	Universal
Operating Position Operating Temperature Physical	Universal -20C (-4F) to +45C (+113F)
Operating Position Operating Temperature Physical MOL	Universal -20C (-4F) to +45C (+113F) 3.88
Operating Position Operating Temperature Physical MOL MOD	Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years cULus - Certified; cULus - Listed
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.03 Yes 2-Years cULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale

