SATCO NUVO

Project Name

Prepared By



SATCO S21732

4.5W CFF/LED/27K/FR/120V/2CD

Notes

General	
Status	Discontinued
Substitute	S21843
Watts	4.5W
Incandescent Equivalent	40W
Volts	120V
Shape	CA10
Base	Candelabra
ANSI Base	E12
Finish	Frost
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80
Lumens	350L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Lamp Type	Candle
Technology	LED
Electrical	
Power Factor	0.9
Power Factor Operating Position	0.9 Universal
Operating Position	Universal
Operating Position Operating Temperature	Universal
Operating Position Operating Temperature Physical	Universal -20C (-4F) to +40C (+104F)
Operating Position Operating Temperature Physical MOL	Universal -20C (-4F) to +40C (+104F) 3.88
Operating Position Operating Temperature Physical MOL MOD	Universal -20C (-4F) to +40C (+104F) 3.88 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	Universal -20C (-4F) to +40C (+104F) 3.88 1.38
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited cULus Damp
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited cULus Damp Yes
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited cULus Damp Yes ESID-2348459
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID CA T20 / T24 Rationale	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited cULus Damp Yes ESID-2348459 Non-Compliant - <82 CRI
Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star ES Unique ID CA T20 / T24 Rationale California Status	Universal -20C (-4F) to +40C (+104F) 3.88 1.38 0.03 Yes 3 Year Limited cULus Damp Yes ESID-2348459 Non-Compliant - <82 CRI Non-Compliant

Safety Listing	cULus
Location Rating	Damp
Energy Star	Yes
ES Unique ID	ESID-2348459
CA T20 / T24 Rationale	Non-Compliant - <82 CRI
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
SDS Sheet	LED_Lamp