SATCO' NUVO

Project Name

Location

Prepared By



Notes

StatusActiveWatts5.5WIncandescent Equivalent60WVolts120VShapeB11BaseCandelabraANSI BaseE12FinishClearCCT (Kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableProduct CategoryCandelTechnologyEDElectrical200Product CategoryCandleTechnology0HzPower Factor0.74Operating Frequency60HzPower Factor0.74Operating ColorNoneWold3.97MOD1.38Housing ColorNoneWeight (Ib.)0.071Additional InformationYesSafety ListingCulus - ListedLocation RatingWetUL ApplicationFilament LED LampCation RatingWetUL ApplicationFilament LED LampCatior RatingKesSofety ListingCulus - ListedCocorpliantYesSofety CompliantYesSofety CompliantYesSofety CompliantYesSofety ListingCulus - ListedCatior RatingKetSofety ListingCulus - ListedCompliantYesSofety ListingCulus - ListedCompliantYesSofety ListingLawful	General	
Incandescent Equivalent60WVolts120VShapeB11BaseCandelabraANSI BaseE12FinishClearCCT (Kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableProduct CategoryCandleTechnologyLEDElectrical0.74Operating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalNoneWeight (lb.)0.071Additional InformationSagaRated For Enclosed FixtureYesWarranty2-YearsComplianceCulus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaSafety ListingCulus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaRotS CompliantYesFCC CompliantYes	Status	Active
Volts120VShapeB11BaseCandelabraANSI BaseE12FinishClearCCT (Kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableDimmableYes-DimmableDimmable120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.74Operating Tenguency60HzOperating Temperature0.74Operating Temperature3.97MOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationYesSafety ListingCULus - ListedLocation RatingWetUL ApplicationFilament LED LampCatior RatingWetSafety ListingLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaRotS CompliantYesFCC CompliantYes	Watts	
Volts120VShapeB11BaseCandelabraANSI BaseE12FinishClearCCT (Kelvin)5000KTemperatureNatural LightCR90+Lumens500LBeam Spread300DimmableYes-DimmableDimmable120V onlyHours Rated15000Product CategoryCandleCethrologyLEDElectrical90+Operating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)Physical1.38Housing ColorNoneWeight (lb.)0.071Additional Information2-YearsSafety ListingCULus - ListedLocation RatingWetUL ApplicationFilament LED LampCatifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaRed FOC CompliantYes	Incandescent Equivalent	60W
BaseCandelabraANSI BaseE12FinishClearCCT (kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating FrequencyOperating Frequency60HzPower Factor0.74Operating ColorNoneWold3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationYesSafety ListingCullus - ListedLocation RatingWetUL ApplicationFilament LED LampCation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRotS CompliantYes		120V
ANSI BaseE12FinishClearCCT (Kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableDimmableYes-DimmableDimmable120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical90+Operating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalNoneMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationYesRated For Enclosed FixtureYesSafety ListingCULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for saleRoHS CompliantYes	Shape	B11
FinishClearCCT (Kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical00Operating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)Physical1.38Housing ColorNoneWeight (lb.)0.071Additional InformationYesSafety ListingcULus - ListedComplianceYesSafety ListingCulcus - ListedCation RatingWetCalifornia StatusLawful for saleRobS CompliantFiesRobS CompliantYesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFiesCompliantFies	Base	Candelabra
CCT (Kelvin)5000KTemperatureNatural LightCRI90+Lumens500LBeam Spread300DinmableYes-DinmableDimmobleYes-DinmableDimmable120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.74Operating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOLMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional Information2-YearsComplianceYesSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYes	ANSI Base	E12
TemperatureNatural LightCRI90+Lumens500LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyEDElectrical0perating FrequencyOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)Physical1.38Housing ColorNoneWeight (lb.)0.071Additional Information2.YearsRated For Enclosed FixtureYesWarranty2.YearsComplianceCullus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for saleRotS CompliantYesFCC CompliantYes	Finish	Clear
CRI90+Lumens500LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0Operating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)Physical1.38MOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional Information2.YearsComplianceSafety ListingSafety ListingCULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRotS CompliantYesFCC CompliantYes	CCT (Kelvin)	5000K
Lumens500LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0perating FrequencyOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)Physical	Temperature	Natural Light
Beam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (Ib.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for saleRoHS CompliantYesFCC CompliantYes	CRI	90+
DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalImage: Colspan="2">Image: Colspan="2">Image: Colspan="2">Colspan="2"Dimming Note120V onlyProduct CategoryCandleTechnologyLEDCandle	Lumens	500L
Dimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationYesRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Beam Spread	300
Hours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingCULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Dimmable	Yes-Dimmable
Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingCULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Dimming Note	120V only
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYes	Hours Rated	15000
ElectricalOperating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (Ib.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYes	Product Category	Candle
Operating Frequency60HzPower Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (Ib.)0.071Additional InformationYesRated For Enclosed FixtureYesWarranty2-YearsSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Technology	LED
Power Factor0.74Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for saleRoHS CompliantYes	Electrical	
Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Operating Frequency	60Hz
PhysicalMOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Power Factor	0.74
MOL3.97MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Operating Temperature	-20C (-4F) to +45C (+113F)
MOD1.38Housing ColorNoneWeight (lb.)0.071Additional InformationImage: Color of the second se	Physical	
Housing ColorNoneWeight (Ib.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	MOL	3.97
Weight (lb.)0.071Additional InformationRated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	MOD	1.38
Additional Information Rated For Enclosed Fixture Yes Warranty 2-Years Compliance Enclosed Fixture Safety Listing cULus - Listed Location Rating Wet UL Application Filament LED Lamp California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale RoHS Compliant Yes FCC Compliant Yes	Housing Color	None
Rated For Enclosed FixtureYesWarranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleROHS CompliantYesFCC CompliantYes	Weight (lb.)	0.071
Warranty2-YearsComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Additional Information	
ComplianceSafety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Rated For Enclosed Fixture	Yes
Safety ListingcULus - ListedLocation RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Warranty	2-Years
Location RatingWetUL ApplicationFilament LED LampCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleRoHS CompliantYesFCC CompliantYes	Compliance	
UL Application Filament LED Lamp California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale RoHS Compliant Yes FCC Compliant Yes	Safety Listing	cULus - Listed
California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale RoHS Compliant Yes FCC Compliant Yes	Location Rating	Wet
California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale RoHS Compliant Yes FCC Compliant Yes		Filament LED Lamp
RoHS Compliant Yes FCC Compliant Yes	California Status	Lawful for sale in California
FCC Compliant Yes	Title 20 / 24 Status	Lawful for sale
· · · · · · · · · · · · · · · · · · ·	RoHS Compliant	Yes
SDS Sheet LED_Lamp	FCC Compliant	Yes
	SDS Sheet	LED_Lamp

