## SATCO' NUVO

Project Name

cation

Prepared By



5.5A15/CL/LED/927/E12/2CD

General	
Status	Active
Watts	5.5W
Incandescent Equivalent	40W
Volts	120V
Shape	A15
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	2700К
Temperature	Warm White
CRI	90+
Lumens	450L
Beam Spread	300
Dimmable	Yes-Dimmable
Dimming Note	120V only
Hours Rated	15000
Product Category	Туре А
Technology	LED
Electrical	
Electrical	
Operating Frequency	60Hz
	60Hz 0.76
Operating Frequency	
Operating Frequency Power Factor	0.76
Operating Frequency Power Factor Operating Temperature	0.76
Operating Frequency Power Factor Operating Temperature Physical	0.76 -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Temperature Physical MOL	0.76 -20C (-4F) to +45C (+113F) 3.43
Operating Frequency Power Factor Operating Temperature Physical MOL MOD	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071 Yes
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071 Yes
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071 Yes 2-Years
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071 Yes 2-Years CULus - Certified; cULus - Listed
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071 Yes 2-Years CULus - Certified; cULus - Listed Wet
Operating Frequency Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.76 -20C (-4F) to +45C (+113F) 3.43 1.85 None 0.071 Yes 2-Years CULus - Certified; cULus - Listed Wet Lawful for sale in California

SDS Sheet

LED\_Lamp

