SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	5.5W
Incandescent Equivalent	60W
Volts	120V
Shape	B11
Base	Medium
ANSI Base	E26
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	90+
Lumens	500L
Beam Spread	300
Dimmable	Yes-Dimmable
Dimming Note	120V only
Hours Rated	15000
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Electrical Operating Frequency	60Hz
	60Hz 0.75
Operating Frequency	
Operating Frequency Power Factor	0.75
Operating Frequency Power Factor Operating Position	0.75 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	0.75 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.75 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.75 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07 Yes 2-Years cETLus - Listed
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07 Yes 2-Years cETLus - Listed Wet
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating UL Application California Status	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07 Yes 2-Years cETLus - Listed Wet Filament LED Lamp
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating UL Application	0.75 Universal -20C (-4F) to +45C (+113F) 3.58 1.38 None 0.07 Yes 2-Years cETLus - Listed Wet Filament LED Lamp Lawful for sale in California

Compliance	
Safety Listing	cETLus - Listed
Location Rating	Wet
UL Application	Filament LED Lamp
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp