

Project Name

Location

Prepared By



# SATCO S21917

10T8/LED/48/5CCT/DR

## Notes

(www) 04-13-2023 00:25:19

## General

Status	Active
Watts	10W
Fluorescent Equivalent	32W/30W/28W/25W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	1700L/1750L/1850L/1850L/1800L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

## Electrical

Ballasting Requirements	Ballast required, check compatibility
Operating Frequency	50/60Hz
Dimming Type	Phase cut
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

## Physical

MOL	47.78
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.47

## Additional Information

Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs

## Compliance

Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-6222FT
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp