

Project Name

Location

Prepared By



SATCO S21918

13T8/LED/48/5CCT/DR

Notes

(www) 18-17-0025 01-20-07

General

Status	Active
Watts	13W
Fluorescent Equivalent	32W/30W/28W/25W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3000K/3500K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	2100L/2150L/2250L/2250L/2200L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast required, check compatibility
Operating Frequency	50/60Hz
Dimming Type	Phase cut
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	47.78
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.47

Additional Information

Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-54T8SL
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp