



Notes

w] 10-27-2025 05:

Status	Active	
Watts	40W	
Incandescent Equivalent	125W	
Fluorescent Equivalent	59W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	Т8	
Base	Single Pin	
ANSI Base	Fa8	
Nominal Length	96	
Finish	White	
CCT (Kelvin)	6500K	
Temperature	Daylight	
CRI	80+	
Lumens	5500L	
Beam Spread	210	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	93.88
MOD	1
Material	Glass
Lens Finish	White
Housing Color	White
Weight (lb.)	0.88

Additional Information		
Additional Info	Suitable for Emergency Lighting only with Satco EM Driver #S8002	
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLXALFHWUTHG
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp